


Serenity Wall Basin Set 160/185/220mm Offset Spout

Nero




Lead Free



Version: 202606



Drawing



Specifications

Watermark License

WM-060073

Temperature Rating

Min 1°C - Max 75°C

Pressure Rating

Min 150kpa - Max 500kpa

Group Item

- 1 x Serenity Wall Basin Set Offset Spout Body Only, SKU:24C021
- 1 x Serenity Wall Basin Set 160/185/220mm Offset Spout Trim Kit Only

*This product is packaged separately.

*Dimensions are nominal measurements only

**Includes an additional non-restricting aerator for bath use



Chrome



Gun Metal



Brushed Bronze



Matte Black



Brushed Gold



Brushed Nickel



Rome Bronze



Tumbled Antique Brass

Serenity Wall Basin Set 160mm Offset Spout With Carrara Handle

24D053BZ/ 24D053BG / 24D053BN/24D053GM / 24D053MB / 24D053CH

Serenity Wall Basin Set 160mm Offset Spout With Verde Alpi Handle

24D054BZ/ 24D054BG / 24D054BN/24D054GM / 24D054MB / 24D054CH

Serenity Wall Basin Set 160mm Offset Spout With Rome Travertine Handle

24D055BZ/ 24D055BG / 24D055BN/24D055GM / 24D055MB / 24D055CH

Serenity Wall Basin Set 160mm Offset Spout With Arabescato Corchia Handle

24D056BZ/ 24D056BG / 24D056BN/24D056GM / 24D056MB / 24D056CH

Serenity Wall Basin Set 160mm Offset Spout With Metal Handle

24D058BZ/ 24D058BG / 24D058BN/24D058GM / 24D058MB / 24D058CH

Serenity Wall Basin Set 160mm Offset Spout With Marquina Black Handle

24D124BZ/ 24D124BG / 24D124BN/24D124GM / 24D124MB / 24D124CH

Serenity Wall Basin Set 185mm Offset Spout With Carrara Handle

24D059BZ/ 24D059BG / 24D059BN/24D059GM / 24D059MB / 24D059CH

Serenity Wall Basin Set 185mm Offset Spout With Verde Alpi Handle

24D060BZ/ 24D060BG / 24D060BN/24D060GM / 24D060MB / 24D060CH

Serenity Wall Basin Set 185mm Offset Spout With Rome Travertine Handle

24D061BZ/ 24D061BG / 24D061BN/24D061GM / 24D061MB / 24D061CH

Serenity Wall Basin Set 185mm Offset Spout With Arabescato Corchia Handle

24D062BZ/ 24D062BG / 24D062BN/24D062GM / 24D062MB / 24D062CH

Serenity Wall Basin Set 185mm Offset Spout With Metal Handle

24D064BZ/ 24D064BG / 24D064BN/24D064GM / 24D064MB / 24D064CH

24D064RB/ 24D064TA

Serenity Wall Basin Set 185mm Offset Spout With Marquina Black Handle

24D125BZ/ 24D125BG / 24D125BN/24D125GM / 24D125MB / 24D125CH

Serenity Wall Basin Set 220mm Offset Spout With Carrara Handle

24D065BZ/ 24D065BG / 24D065BN/24D065GM / 24D065MB / 24D065CH

Serenity Wall Basin Set 220mm Offset Spout With Verde Alpi Handle

24D066BZ/ 24D066BG / 24D066BN/24D066GM / 24D066MB / 24D066CH

Serenity Wall Basin Set 220mm Offset Spout With Rome Travertine Handle

24D067BZ/ 24D067BG / 24D067BN/24D067GM / 24D067MB / 24D067CH

Serenity Wall Basin Set 220mm Offset Spout With Arabescato Corchia Handle

24D068BZ/ 24D068BG / 24D068BN/24D068GM / 24D068MB / 24D068CH

Serenity Wall Basin Set 220mm Offset Spout With Metal Handle24D070BZ/ 24D070BG / 24D070BN/24D070GM / 24D070MB / 24D070CH
24D070RB/ 24D070TA**Serenity Wall Basin Set 220mm Offset Spout With Marquina Black Handle**

24D126BZ/ 24D126BG / 24D126BN/24D126GM / 24D126MB / 24D126CH

Installation Instruction

GENERAL INSTRUCTIONS:

- This product must be installed by a licensed plumber. Ensure that the installation complies with the Australian/New Zealand Standard AS/NZS 3500.
- All pipework must be thoroughly flushed prior to the installation of the mixer. In-line filters must be fitted on both hot and cold supplies to prevent foreign particles from damaging the ceramic cartridge.
- All outlets used primarily for personal hygiene must deliver water at a safe temperature in accordance with regional regulations.

NOTE:

- Do not hydrostatic test the installation with this mixer installed. Damage to the ceramic cartridge may occur.
- Do not remove the ceramic cartridge from the mixer when installing.
- After installation, all connections must be checked for leaks.
- This mixer is not recommended for use in uncontrolled heating systems such as wet-backs or solar heating units unless a suitable tempering valve is fitted.
- If limited water flow is experienced, locate aerator and filter washers and clean away foreign material as required.
- It is the responsibility of the plumber to ensure a waterproof seal is achieved between the product and mounting surface. If in doubt about the quality of the seal, remove the product and reinstall.
- The marble stone hand wheel crafted from natural marble. Each handle boasts unique variations in color, veining, and texture, making every piece one of a kind.


MAINTENANCE AND CARE:

- Regularly check the mixer and connections for signs of wear or leaks.
- Clean the tap with mild soapy water to maintain its appearance, avoiding harsh chemicals and abrasive materials that may damage the finish.
- Avoid contact with highly pigmented substances such as red wine, coffee and ink, as they may cause permanent staining.


FINAL INSPECTION:



- Ensure the tap operates smoothly and that there are no leaks at the connections.
- Clean the area and the newly installed tap with a soft cloth to remove any installation residues.

Installation Instruction For Body



1. Remove the components from spindle as shown in the provided diagram. Ensure all parts are removed gently to avoid damage to the components or threads.






2. Position the mixer body against the nogging and secure it firmly. Ensure the installation depth is 60–75mm from the nogging to the ceramic tile.


Note: The U-shaped fixing clip must be used to secure the main body. Install the U-shaped clip at a distance of 70–80mm from the center of the main body to ensure it remains stable and does not move.


3. Connect the cold and hot water supply lines and perform a leak test.

4. Drill three Ø40mm holes in the plasterboard as shown in the diagram.




5. Install plasterboard and waterproof the gap between the mixer body and plasterboard.





6. Drill three Ø35mm holes in the ceramic tile aligned with the plasterboard cutouts.


7. Position the ceramic tile precisely and waterproof the junction between the mixer body.



8. Reattach the locking nuts onto the spindle.


Note: Use the provided washers to achieve a secure and watertight connection.

Attach the gauges to the spindle.



Trim any excess thread

9. Trim any excess thread. Remove the gauges after this step.



Spindle Adaptor




O-Ring

Screw


10. Install the spindle adaptors onto the spindles. Tighten the spindle adaptors securely using screws, ensuring that O-rings are properly seated.

Installation Instruction


For Trim Kit Only



1. Release the grub screws to remove the water testing plug.



2. Slide the backplate and washer onto the wall. Ensure the spout is aligned and secure it firmly using the supplied grub screw.



3. Apply lubrication evenly to the O-Ring. Refer to the diagram to identify the correct O-Ring position. Ensure the O-Ring is well-lubricated to prevent damage during installation.

For Metal Handwheels:

Rotate the left spindle adaptor clockwise to its fully closed position.

Rotate the right spindle adaptor counterclockwise to its fully closed position.

Refer to the diagram for clarification.

For Marble Handwheels:

No adjustment to the spindle adaptor is necessary.

Align the Handwheel with the Spindle Adaptor:

Ensure the spline on the underside of the handwheel align perfectly with the gears on the spindle adaptor, as shown in the above diagram.


This alignment is crucial for proper functionality.

Secure the Handwheel:

Once aligned, press the handwheel down firmly onto the spindle adaptor.

Tip:

For metal handwheels, ensure the handwheel marked "H" is installed on the left side and the handwheel marked "C" is installed on the right side.



4. Turn on the drainage system and water supply, and inspect all connections for any signs of leakage.

Note: If you bought marble handwheel product, there are no hot/cold markings are applied to the handwheels.

Nero

