

Mecca


Wall Basin/Bath Mixer

Separate Back Plate

Nero




Lead Free



Version:202605




Drawing	Specifications	Group Item										
	Watermark License WM-060073 Temperature Rating Min 1°C-Max 75°C Pressure Rating Min 150kpa - Max 500kpa	1x Universal Body 1x Trim Kit Only										
	Finish & SKU <table><tr><td> Chrome NR221910c(120/160/185/230/260)CH</td><td> Gun Metal NR221910c(120/160/185/230/260)GM</td></tr><tr><td> Matte Black NR221910c(120/160/185/230/260)MB</td><td> Brushed Gold NR221910c(120/160/185/230/260)BG</td></tr><tr><td> Brushed Bronze NR221910c(120/160/185/230/260)BZ</td><td> Brushed Nickel NR221910c(120/160/185/230/260)BN</td></tr><tr><td> Matte White NR221910c(120/160/185/230/260)MW</td><td> Rome Bronze NR221910c(160/185/230)RB</td></tr><tr><td> Tumbled Antique Brass NR221910c(160/185/230)TA</td><td></td></tr></table>	 Chrome NR221910c(120/160/185/230/260)CH	 Gun Metal NR221910c(120/160/185/230/260)GM	 Matte Black NR221910c(120/160/185/230/260)MB	 Brushed Gold NR221910c(120/160/185/230/260)BG	 Brushed Bronze NR221910c(120/160/185/230/260)BZ	 Brushed Nickel NR221910c(120/160/185/230/260)BN	 Matte White NR221910c(120/160/185/230/260)MW	 Rome Bronze NR221910c(160/185/230)RB	 Tumbled Antique Brass NR221910c(160/185/230)TA		
 Chrome NR221910c(120/160/185/230/260)CH	 Gun Metal NR221910c(120/160/185/230/260)GM											
 Matte Black NR221910c(120/160/185/230/260)MB	 Brushed Gold NR221910c(120/160/185/230/260)BG											
 Brushed Bronze NR221910c(120/160/185/230/260)BZ	 Brushed Nickel NR221910c(120/160/185/230/260)BN											
 Matte White NR221910c(120/160/185/230/260)MW	 Rome Bronze NR221910c(160/185/230)RB											
 Tumbled Antique Brass NR221910c(160/185/230)TA												
	*Dimensions are nominal measurements only **Includes an additional non-restricting aerator for bath use											

Installation Instruction For Body

GENERAL INSTRUCTIONS:

- This product must be installed by a licensed plumber. Ensure that your plumbing installation conforms to the Australian/New Zealand Standard AS/NZS 3500.
- All pipework must be thoroughly flushed prior to the installation of the mixer. In-line filters must be fitted on both hot and cold supplies to prevent foreign particles from damaging the ceramic cartridge.
- All outlets used primarily for personal hygiene must deliver water at a safe temperature in accordance with regional regulations.




1. Secure the mixer body (1) to the nogging, ensuring an installation depth of 51-68mm from the nogging to the ceramic tile.

Note: Do not remove the plastic sleeve (2) from the mixer body.

2. Connect the cold and hot water supply lines and perform a leak test.


3. Drill a ø50mm and a ø40mm hole in the plasterboard for mixer body installation, and then position the plasterboard as shown in the above image.




4. Mark the plastic sleeve (2) 4-7mm from the ceramic tile surface to the body and waterproof the gap between the plasterboard and body.

5. Remove the self-tapping screw, washer, and plastic sleeve, then cut the sleeve at the marked point.


6. Reattach the self-tapping screw, washer, and plastic sleeve.




7. Waterproof the gap between the plasterboard and body




Installation Instruction For Trim Kit Only



1. Drill a Ø50mm and a Ø40mm hole in the ceramic tile, then position it as shown in the above diagram.
2. Undo the self-tapping screw to remove the plastic sleeve, and release the grub screws to remove the water testing plug.



3. Insert the O ring to the cartridge bell groove, and slide the dressing ring onto cartridge.
4. Apply waterproof treatment to the area indicated in the diagram above.
5. Tighten up the dressing ring on the cartridge bell.



6. Slide the plate and washer onto the wall, set the spout in place, and secure it tightly using the grub screw.
7. Slide the plate onto the wall, attach the washer to the cartridge rod, position the handle, tighten it with a grub screw using an Allen key, and cap the grub screw hole.

Please note: there is a washer between backplate and the spout.

MAINTENANCE AND CARE:

- Regularly check the mixer and connections for signs of wear or leaks.
- Clean the tap with mild soapy water to maintain its appearance, avoiding harsh chemicals and abrasive materials that may damage the finish.

FINAL INSPECTION:

- Ensure the tap operates smoothly and that there are no leaks at the connections.
- Clean the area and the newly installed tap with a soft cloth to remove any installation residues.

Nero

