


Mecca Shower Mixer 60mm Plate


Nero



Lead Free



Version: 202606



Drawing	Specifications	Group Item											
	Watermark License WM-060073 Temperature Rating Min 1°C-Max 75°C Pressure Rating Min 150kpa - Max 500kpa	1x Universal Body 1x Trim Kit Only											
	Finish & SKU <table><tr><td> Chrome NR221911hCH</td><td> Gun Metal NR221911hGM</td><td> Brushed Bronze NR221911hBZ</td><td> Brushed Nickel NR221911hBN</td></tr><tr><td> Matte Black NR221911hMB</td><td> Brushed Gold NR221911hBG</td><td> Matte White NR221911hMW</td><td> Rome Bronze NR221911hRB</td></tr><tr><td> Tumbled Antique Brass NR221911hTA</td><td colspan="3"></td></tr></table>	 Chrome NR221911hCH	 Gun Metal NR221911hGM	 Brushed Bronze NR221911hBZ	 Brushed Nickel NR221911hBN	 Matte Black NR221911hMB	 Brushed Gold NR221911hBG	 Matte White NR221911hMW	 Rome Bronze NR221911hRB	 Tumbled Antique Brass NR221911hTA			
 Chrome NR221911hCH	 Gun Metal NR221911hGM	 Brushed Bronze NR221911hBZ	 Brushed Nickel NR221911hBN										
 Matte Black NR221911hMB	 Brushed Gold NR221911hBG	 Matte White NR221911hMW	 Rome Bronze NR221911hRB										
 Tumbled Antique Brass NR221911hTA													

*Dimensions are nominal measurements only.

Installation Instruction For Body Only



→ GENERAL INSTRUCTIONS:

- This product must be installed by a licensed plumber. Ensure that your plumbing installation conforms to the Australian/New Zealand Standard AS/NZS 3500.
- All pipework must be thoroughly flushed prior to the installation of the mixer. In-line filters must be fitted on both hot and cold supplies to prevent foreign particles from damaging the ceramic cartridge.
- All outlets used primarily for personal hygiene must deliver water at a safe temperature in accordance with regional regulations.




1. Secure the mixer body (1) to the nogging, ensuring an installation depth of 51-68mm from the nogging to the ceramic tile. Note: Do not remove the plastic sleeve (2) from the mixer body.
2. Connect the cold and hot water supply lines and perform a leak test.
3. Drill a $\phi 50$ mm hole in the plasterboard for mixer body installation, and then position the plasterboard as shown in the above image.

4. Mark the plastic sleeve (2) 4-7mm from the ceramic tile surface to the body and waterproof the gap between the plasterboard and body.
5. Remove the self-tapping screw, washer, and plastic sleeve, then cut the sleeve at the marked point.
6. Reattach the self-tapping screw, washer, and plastic sleeve.




7. Waterproof the gap between the plasterboard and body.

Installation Instruction For Trim Kit Only



1. Drill a Ø50mm hole in the ceramic tile, then position it as shown in the above diagram.
2. Undo the self-tapping screw, washer, plastic sleeve.

3. Insert the O ring to the dressing bell groove, and slide the dressing bell onto cartridge.
4. Apply waterproof treatment to the area in the diagram above.
5. Tighten the dressing ring on the dressing bell.



6. Slide the backplate onto the wall.
7. Attach the washer to the cartridge rod, position the handle, tighten it with a grub screw using an Allen key, and cap the grub screw hole.

MAINTENANCE AND CARE:

- Regularly check the mixer and connections for signs of wear or leaks.
- Clean the tap with mild soapy water to maintain its appearance, avoiding harsh chemicals and abrasive materials that may damage the finish.

FINAL INSPECTION:

- Ensure the tap operates smoothly and that there are no leaks at the connections.
- Clean the area and the newly installed tap with a soft cloth to remove any installation residues.

Nero

